



RIBCRAFT 12.5m PRO: Standard Features. Including the following items:

- Overall Length: 12.5 Metres.
- Overall Beam: 3.5 Metres.
- Commercial Specification Ribcraft deep V hull (GRP).
- Commercial Specification 1500 gsm Orca 866 Hypalon inflation tubes with colour of choice.
- 11 x Over Pressure Release Valves, One per chamber.
- Heavy Duty 'D' section rubbing strake fendering.
- Anti-slip decking finish.
- External tube looped lifelines, with 'D' ring tube patches.
- Under deck trunking system for all cables.
- Aft deck water collection sump.
- Elephant trunk style deck drainer 4" minimum.
- Stainless steel bow winch eye strong point and transom mounted towing eyes.
- Anchor locker, hatch and deck tie off cleat.
- Foot pump and emergency tube repair kit.



Package Layout 1

Includes:

- Standard Equipment.
- Touring double console with access hatch, windscreen and surrounding stainless steel grab rail.
- Capacity for up to 12 passengers either one person jockey seats or bench seating configuration
- Heavy-duty stainless steel double A-frame.
- Twin Seastar Hydraulic Steering System.
- Twin Installation Suzuki DF300 APXX.



Package Layout 2

Includes:

- Standard Equipment.
- Partially enclosed Cabin constructed from GRP with custom console configuration.
- Capacity for up to 12 passengers either one person jockey seats or bench seating configuration
- Heavy-duty stainless steel double A-frame.
- Twin Seastar Hydraulic Steering System.
- Twin Installation Suzuki DF300 APXX.



Package Layout 3

Includes:

- Standard Features.
- Fully enclosed Cabin constructed from GRP with custom console configuration.
- Capacity for up to 12 passengers either one person jockey seats or bench seating configuration.
- Heavy-duty stainless steel double A-frame.
- Twin Seastar Hydraulic Steering System.
- Twin Installation Suzuki DF350 APXX.



RIBCRAFT reserves the right to change the specifications and prices without prior notice. Terms and conditions apply. Please get in touch to get your personalised quotation.



Cert No. 7662

